MAN TGS 41.520 SWAN TSP 47-5 160RZ (47m)

General characteristics

Brand	MAN
Subcategory	Concrete pump
Meter reading	750km
Date of first registration	05-01-2026
Colour	Wit
Fuel	Diesel
Emission class	Euro 6
Reference	MAN TGS 41.520 8x4 SWAN TSP 47-5 160RZ (47m)



Properties

Single weight	32.450kg
GVW	41.000kg
Cabin	No

Technical specifications

Number of axes	4
Axis configuration	8x4
Transmission	Manual transmission
Assets	520hp

Description

EUROMIX TO GO – new vehicles available immediately from stock in Porta Westfalica, Germany. Fully built, direct from the manufacturer – ideal for a short-term capacity increase or a replacement investment. Price negotiable – please contact us. MAN TGS 41.520 BB 8x4 EURO 6e Concrete pump EuromixMTP SWAN TSP 47-5 160RZ - NEW NEW - without registration - without registration - Vehicle equipment: Diesel engine MAN D2676 LFBA, 382 kW (520 hp) power, 2.500 Nm torque, Euro 6e Manual gearbox, MAN 16.25 OD Front axle, 9.200 kg, non-driven, cranked, steered, non-liftable Rear axle, 13.000 kg, hub-reduction axle with through-drive, straight, non-steered, non-liftable Suspension type leaf/leaf (BB) on front axles and driven rear axles Tyres front axle optionally 385/65R22,5 steer-S+G TL (160 K) Tyres rear axle optionally 315/80R22,5 drive-S+G TL (154/150 K) 4.105 mm main wheelbase - 1.795 mm wheelbase between front axles L-plate and low-noise certificate (according to KDV 1967) 390 l fuel tank capacity, 35 l AdBlue tank capacity, ABS - EBS - ESP - FGR - EBA - LDW EuromixMTP - concrete pump SWAN TSP 47-5 160RZ Model: SWAN TSP 47-5 160 RZ Section: concrete pump: Max. theoretical concrete output : 160 m³/hr Max. theoretical concrete pressure : 85 bar Strokes 30 per min Delivery cylinder: Ø230 mm x 2100 mm stroke Main hydraulic cylinder : Ø2100 mm x Ø140 x Ø80 mm Concrete valve: S-valve, water pump: 20 l/min - 170 bar Water tank: 800 l, 12 m hose with spray gun Concrete hopper : 600 litres Lubrication :Lincoln automatic lubrication for hopper group Hydraulic pumps : Rexroth 2xA4VG145, Rexroth A10VO28 Rexroth A17FO045, Blau Ascend AP 20.140/115 Switching system : magnetic sensor (proximity switch) Control box: DIGITEX, waterproof Remote control : Scanreco remote control + 30 m cable Section: boom: Boom S 47-5 (boom 5 sections, RZ folding) Type : RZ folding Max. vertical reach : 46,8 m (without end hose) Max. horizontal reach : 42,8 m (without end hose) End hose : 3m single flange, DN 125 Outrigger type: X-type Slewing ring: 365 degrees Slewing speed: 0.3 RPM Delivery line diameter: 125 mm (outer diameter 132 mm) 5,5" flanges & couplings Control system Outrigger spread front: 8.6 m Outrigger spread rear: 8.7 m Your advantages • Ready for immediate use: concrete pumps, concrete mixers, tippers, hook-lift trucks • Chassis, body and assembly from a single source • Fair prices • Financing in 19 European countries • Trade-in of your used vehicle Your contacts • Denis Omeragic: +49 178 7800047 (German, English, Bosnian, Croatian, Serbian) • Henri Omeragic: +49 178 7800045 (German, Bosnian, Croatian, Serbian) • Harun Cevik: +49 173 5100933 (German, English, Turkish) • Jamila Azzi: +49 160 96667822 (French, Arabic) • Olga Tissen: +49 170 7457091 (German, Russian) • Karolina Cyburt: +49 151 72011958 (Polish) EuromixMTP GmbH, Gänsekamp 7, 32457 Porta Westfalica, Germany info@euromix.de | www.euromix.de

Accessories

- Apple CarPlay
- Bluetooth
- Differential Lock
- ESP
- Air Suspension Seats
- Air conditioning
- Leaf spring suspension
- Navigation system
- Heavy duty engine brake
- Visor
- Radio/Cd/Audio system
- EBS
- Climate control
- ASR (Anti-Slip Regulation/Traction Control)