Mercedes-Benz Arocs 4142 Arocs 5 4142 8x4 SWAN TSP 47-5 160RZ (47m)

General characteristics

Brand	Mercedes-Benz
Model	Arocs 4142
Subcategory	Concrete pump
Meter reading	750km
Date of first registration	29-12-2025
Colour	Wit
Fuel	Diesel
Emission class	Euro 6
Reference	Mercedes Arocs 5 4142 8x4 SWAN TSP 47-5 160RZ (47m)



Properties

GVW	44.000kg
Cabin	No

Technical specifications

Number of axes	4
Axis configuration	8x4
Transmission	Automatic
Assets	420hp

Description

EUROMIX TO GO – new vehicles available immediately from stock in Porta Westfalica, Germany. Fully built, direct from the manufacturer – ideal for a short-term capacity increase or a replacement investment. Price negotiable – please contact us. Mercedes-Benz Arocs 5 4142 8x4 Euro 6e Concrete pump EuromixMTP SWAN TSP 47-5 160RZ (Rental possible) - NEW NEW - without registration - without registration - Vehicle equipment: Engine OM471, R6, 12,8 l, 308 kW (420 hp), 2500 Nm Gearbox G 330-12/11,63-0,77 driving programme offroad PowerShift 3 automated Front axle 7,5 t Rear axle ring gear 300 hub reduction, 13,4 t Tyres front axle 315/80 R 22,5 Tyres rear axle 315/80 R 22,5 Wheelbase 5450 mm S-cab ClassicSpace, 2,30 m, tunnel 170 mm Disc brakes, on front and rear axles Tank 290 l, left, 650 x 565 x 950 mm, steel AdBlue tank 25 l Cab rear wall, with window - tinted windscreen Steering, Servotwin, 4-axle and 9t front axle, air Electronic braking system with ABS and ASR ABS Parking brake, electronic Cab rear wall, with window Rain sensor Pre-installation for reversing camera EuromixMTP - concrete pump SWAN TSP 47-5 160RZ Model: SWAN TSP 47-5 160 RZ Section: concrete pump: Max. theoretical concrete output : 160 m³/hr Max. theoretical concrete pressure : 85 bar Strokes 30 per min Delivery cylinder: Ø230 mm x 2100 mm stroke Main hydraulic cylinder : Ø2100 mm x Ø140 x Ø80 mm Concrete valve: S-valve, water pump: 20 l/min - 170 bar Water tank: 800 l, 12 m hose with spray gun Concrete hopper : 600 litres Lubrication :Lincoln automatic lubrication for hopper group Hydraulic pumps : Rexroth 2xA4VG145, Rexroth A10VO28 Rexroth A17FO045, Blau Ascend AP 20.140/115 Switching system : magnetic sensor (proximity switch) Control box: DIGITEX, waterproof Remote control : Scanreco remote control + 30 m cable Section: boom: Boom S 47-5 (boom 5 sections, RZ folding) Type : RZ folding Max. vertical reach : 46,8 m (without end hose) Max. horizontal reach : 42,8 m (without end hose) End hose : 3m single flange, DN 125 Outrigger type: X-type Slewing ring: 365 degrees Slewing speed: 0.3 RPM Delivery line diameter: 125 mm (outer diameter 132 mm) 5,5" flanges & couplings Control system Outrigger spread front: 8.6 m Outrigger spread rear: 8.7 m Your advantages • Ready for immediate use: concrete pumps, concrete mixers, tippers, hook-lift trucks • Chassis, body and assembly from a single source • Fair prices • Financing in 19 European countries • Trade-in of your used vehicle Your contacts • Denis Omeragic: +49 178 7800047 (German, English, Bosnian, Croatian, Serbian) • Henri Omeragic: +49 178 7800045 (German, Bosnian, Croatian, Serbian) • Harun Cevik: +49 173 5100933 (German, English, Turkish) • Jamila Azzi: +49 160 96667822 (French, Arabic) • Olga Tissen: +49 170 7457091 (German, Russian) • Karolina Cyburt: +49 151 72011958 (Polish) EuromixMTP GmbH, Gänsekamp 7, 32457 Porta Westfalica, Germany info@euromix.de | www.euromix.de

Accessories

- Bluetooth
- Differential Lock
- ESP
- Air conditioning
- Leaf spring suspension
- Central locking
- Heavy duty engine brake
- Visor
- EBS
- ASR (Anti-Slip Regulation/Traction Control)