Mercedes-Benz Arocs 4142 Mercedes-Benz AROCS 5 4142 B 8X4 Euro 3 EuromixMTP EM 10

General characteristics

Brand	Mercedes-Benz
Model	Arocs 4142
Subcategory	Concrete mixer
Year of construction	2026
Colour	Wit
Fuel	Diesel
Emission class	Euro 3
Reference	MB 4142 8x4 2026



Properties

GVW	41.000kg

Technical specifications

Number of axes	4
Axis configuration	8x4
Transmission	CVT automatic transmission
Assets	420hp

Description

EUROMIX TO GO – new vehicles available immediately from stock in Porta Westfalica, Germany. Fully built, direct from the manufacturer – ideal for a short-term capacity increase or a replacement investment. Price negotiable – please contact us. Mercedes-Benz Arocs model generation 5 4142 8x4 EURO 3 3X AVAILABLE EuromixMTP EM 10 R - NEW NEW - without registration - without registration - Vehicle equipment: Engine OM460, R6, 12,8 l, 310 kW (421 hp), 2100 Nm Euro 3 Front axle 7,5 t Rear axle ring gear 300 hub reduction, 13,4 t Tyres front axle 315/80 R 22,5 Tyres rear axle 315/80 R 22,5 Wheelbase 4550 mm Manual gearbox Cab S-cab Classic Space Disc brakes, on front and rear axles Tank 290 l, left, 735 x 700 x 750 mm, Cab rear wall, with window - tinted windscreen Light sensor - daytime running lights Roof hatch/roof ventilation flap External sun visor, transparent Multifunction steering wheel Classic Cockpit Air conditioning Cruise control Vehicle class N3G, off-road vehicle Truck mixer equipment EuromixMTP - truck mixer body EM 10 R - Regular Model: EM 10 R Nominal volume 10m³ ready-mix concrete Mixing drum in regular design Mixing drum in regular version made of S355 Mixing spirals in regular version made of S420 MC Gearbox make ZF - P5300 Hydraulic pump make Bosch Rexroth Hydraulic motor make Bosch Rexroth Integrated oil cooling system Mechanical mixer control and electric start/stop Compressed-air water system Water connection at the platform with hose line Water filling line, one side with C-coupling Mixing drum with one service hatch Access ladder with platform Rubber attachment on the charging hopper Swivelling single-arm steel discharge chute Wear plates in charging hopper, discharge bowl and swivel chute Drum lock to secure the drum during maintenance Polyurethane primer Weight approx. 4.250kg, deviations +/- 5% with emergency stop function according to EU safety standards Aluminium mudguards over the rear axles 2x extension chutes made of steel or plastic Water system Water tank 500l (compressed air) Steel water tank Shut-off valve mounted below the water tank in the filling line Water connection „C“ coupling, Controls & electrics Mixer control – mechanical at rear Start/stop system (with EDC) Your advantages • Ready for immediate use: concrete pumps, concrete mixers, tippers, hook-lift trucks • Chassis, body and assembly from a single source • Fair prices • Financing in 19 European countries • Trade-in of your used vehicle Your contacts • Denis Omeragic: +49 178 7800047 (German, English, Bosnian, Croatian, Serbian) • Henri Omeragic: +49 178 7800045 (German, Bosnian, Croatian, Serbian) • Harun Cevik: +49 173 5100933 (German, English, Turkish) • Jamila Azzi: +49 160 96667822 (French, Arabic) • Olga Tissen: +49 170 7457091 (German, Russian) • Karolina Cyburt: +49 151 72011958 (Polish) EuromixMTP GmbH, Gänsekamp 7, 32457 Porta Westfalica, Germany info@euromix.de | www.euromix.de